


LZR[®] - S600

LASER SCANNER FOR BUILDING AUTOMATION AND SECURITY

Commercial sheet



MOVE TO THE 4TH DIMENSION ON YOUR SECURITY SYSTEM

DESCRIPTION

The **LZR[®]-S600** is a LASER-based security device designed to prevent goods and buildings from theft, vandalism and intrusion. This high-precision sensor ensures high levels of detection and security for your valuables.

It is a compact and competitive solution with easy plug & play and teach-in installation.




PERFORMANCE

- Typical detection range : 10 m × 10 m*.
- Capacity to detect objects in mm-range** and with a remission factor down to 2 %.
- Compared to standard camera system, no external illumination of target necessary.
- Four planes covering a given area in height, width and depth.
- High immunity to environmental interferences due to time of flight with dedicated software.
- Opportunity for retrofit due to easy installation and low commissioning costs.
- Different functions* can be achieved thanks to 2 independent relay outputs : prealert/alert, night and day, anti-vandalism.




* For further options, please contact Sensorio


** Depends on the application




Protection of works of art




Day and night feature : « day »




Day and night feature : « night »



Intrusion protection



Protection against product damage and theft



9.9 m x 9.9 m @ 2 % remission factor

APPLICATIONS

APPLICATIONS

- Protection against theft and vandalism.
- Perimeter protection / intrusion detection.
- Protection of works of art and masterpieces in museums.
- Protection of high level security buildings.

EASE OF INSTALLATION

- 3 visible red LASER beams can be activated to align the detection surface and adjust the tilt and rotation angles.
- Teach-in function: self-learning of both environment and background through an automatic adjustment of the detection planes.
- Remote control to easily set the adjustable parameters.

TECHNICAL SPECIFICATIONS

Technology	LASER scanner, time-of-flight measurement
Detection mode	Movement and presence
Max. detection range @ 2% remission factor	9,9 m x 9,9 m (For further options, please contact Sensorio)
Remission factor	> 2 %
Angular resolution	0,3516°
Typ. min. target size	2,1 cm @ 3 m / 3,5 cm @ 5 m / 7 cm @ 10 m (in proportion to object distance)
Emission characteristics IR LASER	Wavelength 905 nm; max. output pulse power 75 W ; Class 1
Supply voltage	10-35V DC @ sensor terminal
Power consumption	< 5 W
Response time	Typ. 20 ms; max. 80 ms
Output Max. switching voltage Max. switching current	2 electronic relays (galvanic isolated - polarity free) 35V DC / 24V AC 80 mA (resistive)
Input Max. contact voltage Voltage threshold	2 optocouplers (galvanic isolated - polarity free) 30V DC (over-voltage protected) Log. H: > 8V DC Log. L: < 3V DC
LED signals	1 blue LED : power-on status 1 orange LED : error status 2 bicoloured LED : detection/output status (green LED: no detection; red LED: detection)
Dimensions	125 mm (D) x 93 mm (W) x 70 mm (H) (mounting bracket + 14 mm)
Material	PC/ASA (colour: black or white)
Rotation angles on bracket	-5° to +5° (lockable)
Tilt angles on bracket	-3° to +3°
Protection degree	IP65 (avoid direct exposure to high pressure cleaning)
Temperature range	-30°C to +60°C if powered -10°C to +60°C unpowered
Humidity	0-95 % non-condensing
Vibrations	< 2 G
Norm conformity	2006/95/EC: LVD; 2002/95/EC: RoHS; 2004/108/EC: EMC ; EN 60529:2001; IEC 60825-1:2007 Laser Class 1 & 3R; EN 61000-6-2:2005 EMC - Industrial level; EN 61000-6-3:2006 EMC - Commercial level

Specifications are subject to change without prior notice.

DISCLAIMER This document as well as all other enclosed documents (quotation / specification / other) are provided « as is » without warranties of any kind, either expressed or implied, including but not limited to the implied warranties of merchantability, fitness for a particular purpose, or non-infringement. / Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. / BEA has the right without liability to change descriptions and specifications at any time. / Prices, shipping and availability are subject to change without prior notice.



www.sensorio.be

LZR®-S600 LASER SCANNER FOR BUILDING AUTOMATION AND SECURITY

A HALMA COMPANY



BEA s.a. / LIEGE Science Park / Allée des Noisetiers 5 / 4031 Angleur • BELGIUM
T +32 (0) 4 361 65 65 / F +32 (0) 4 361 28 58 / E info@sensorio.be

SENSORIO®